

## CUT160 (RC16)



### Power source contains :

#### Standard:

- Plasma cutting
- Current knob
- 2T/4T switch
- Gas inspection switch
- Air pressure LED
- Protection LED
- Digital display

### Accessories :

#### Standard:

- # 1pc of 6m A141 plasma torch,
- #1set of 300A Earth clamp+3m\*25mm<sup>2</sup> Cable
- +KDP-70A,
- #1 set of air regulator for CUT160

### • Specifications

Products Type	CUT 160
Model	RC16
Input Voltage (V)	AC 415 ± 15%
Frequency (HZ)	50/60
Rated Input Current (A)	44
Power (KVA)	29
No-load Voltage (V)	320
Output Current Range (A)	20-160
Rated Output Voltage (V)	144
Duty Cycle (%)	60
No-load Loss (W)	85
Efficiency (%)	85
Power Factor	0.93
Insulation Grade	F
Housing Protection Grade	IP 21
Arcing Way	Pilot arc transfer
Required Air Pressure (Kg/cm <sup>2</sup> )	0.4-0.6
Cutting Thickness (mm)	1-50
Net Weight (Kg)	60

\* In view of continuous development RALLIWOLF reserves the right to modify / alter the design / modification without prior notice

## Ralli Wolf Industries Ltd.

(Formerly Ralli Engineering Ltd)

An ISO 9001 : 2015 certified Organisation

**Regd. Office :** 4, Fairlie Place Kolkata - 700001 (India), E : info@ralliwolf.com, P : +91 33 2262 7341

SALES NETWORK : Ahmedabad | Akola | Baroda | Bangalore | Bhubaneswar | Bhopal | Chennai | Coimbatore | Cuttack | Delhi  
Faridabad | Guwahati | Indore | Jaipur | Jamshedpur | Kolkata | Ludhiana | Mumbai | Nagpur | Pune | Raipur | Secunderabad | Trichy