



AIR PLASMA CUTTING



• Specifications

Products Type	CUT 60G
Model	RC60
Input Voltage (V)	AC 415 ± 15%
Frequency (HZ)	50/60
Rated Input Current (A)	11
Power (KVA)	7.00
No-load Voltage (V)	268
Output Current Range (A)	20-60
Rated Output Voltage (V)	104
Duty Cycle (%)	60
No-load Loss (W)	60
Efficiency (%)	85
Power Factor	0.93
Insulation Grade	F
Housing Protection Grade	IP 21
Arcing Way	Pilot arc transfer
Required Air Pressure (Kg/cm ²)	4-5
Cutting Thickness (mm)	1-15
Net Weight (Kg)	19

• Features

- Easy to cut metals in a fast and economical way
- Energy Saving
- Pilot-Arc to Extend the Durability of Consumables
- Suitable for cutting stainless steel, copper, carbon steel, aluminium and other metals

• Standard Accessories



* In view of continuous development RALLIWOLF reserves the right to modify / alter the design / modification without prior notice

Ralli Wolf Industries Ltd.

(Formerly Ralli Engineering Ltd)

An ISO 9001 : 2015 certified Organisation

Regd. Office : 4, Fairlie Place Kolkata - 700001 (India), E : info@ralliwolf.com, P : +91 33 2262 7341

SALES NETWORK : Ahmedabad | Akola | Baroda | Bangalore | Bhubaneswar | Bhopal | Chennai | Coimbatore | Cuttack | Delhi
Faridabad | Guwahati | Indore | Jaipur | Jamshedpur | Kolkata | Ludhiana | Mumbai | Nagpur | Pune | Raipur | Secunderabad | Trichy