

ARC SERIES (INVERTER)

MODEL: **ECO-250**

Features

- Electrode 1.6-3.15 mm continuous use
Electrode 4.00 mm -Intermittent use.
- Excellent Arc Strike with inbuilt Arc Force & Hot start.
- Quick & minium maintenance with single PCB design.



Technical Specifications:

| | | | |
|--------------------------|----------------------|---------------------|------------|
| Products Type | : ARC 250 | No-load Loss (W) | : 35 |
| Model | : ECO-250 | Efficiency (%) | : 85 |
| Input Supply (V) | : AC 230V ± 15%, 1Ph | Power Factor | : 0.73 |
| Frequency (HZ) | : 50/60 | Insulation Grade | : F |
| Rated Input Current (A) | : 36 | Protection Grade | : IP21 |
| Power (KVA) | : 8.3 | Inverter Technology | : IGBT |
| No-load Voltage (V) | : 66 | Arc Force Control | : IN BUILT |
| Output Current Range (A) | : 20 - 250 | Net Weight (Kg) | : 7 |
| Rated Output Voltage (V) | : 28 | Welding Accessories | : YES |
| Duty Cycle (%) | 60 | | |

Applications : General Fabrication / Maintenance Works

* In view of continuous development RALLIWOLF reserves the right to modify / alter the design / modification without prior notice

Ralli Wolf Industries Ltd.

An ISO 9001 : 2015 certified Organisation

Corporate Office :

Diamond Heritage, 510, 5th Floor,
16, Strand Road, Kolkata - 700001 (India)
E : info@ralliwolf.com, P : +91 81000 80353
CIN : U51109WB1996PLC077080

Sales Network :

Ahmedabad, Bangalore, Baroda, Bhopal, Chennai, Coimbatore, Cuttack, Delhi, Gurgaon, Guwahati, Jaipur, Jamshedpur, Kolkata, Ludhiana, Mumbai, Nagpur, Pune, Secunderabad, Siliguri, Thiruvananthapuram, Trichy, Vishakhapatnam

Follow us :



www.ralliwolf.com +91 90734 93011