

CUT 160 AIR PLASMA CUTTING

Features

- Plasma cutting
- 2T/4T switch
- Over current LED
- Digital display

MODEL: **RC 16**



Technical Specifications:

Model	: RC16	No-load Loss (W)	: 85
Input Voltage (V)	: 415V ±15%	Efficiency (%)	: 85
Frequency (HZ)	: 50/60	Power Factor	: 0.93
Rated Input Current (A)	: 44	Insulation Grade	: F
Power (KVA)	: 29	Housing Protection Grade	: IP 21
No-load Voltage (V)	: 320	Arcing Way	: Pilot arc transfer
Output Current Range (A)	: 20-160	Required Air Pressure (Kg/cm2)	: 4-6
Rated Output Voltage (V)	: 144	Cutting Thickness (mm)	: 1-50
Duty Cycle (%)	: 60	Net Weight (Kg)	: 60

Ralli Wolf Industries Ltd.

An ISO 9001 : 2015 certified Organisation

Corporate Office :

Diamond Heritage, 510, 5th Floor,
16, Strand Road, Kolkata - 700001 (India)
E : info@ralliwolf.com, P : +91 81000 80353
CIN : U51109WB1996PLC077080

Sales Network :

Ahmedabad, Bangalore, Baroda, Bhopal, Chennai, Coimbatore, Cuttack, Delhi, Gurgaon, Guwahati, Jaipur, Jamshedpur, Kolkata, Ludhiana, Mumbai, Nagpur, Pune, Secunderabad, Siliguri, Thiruvananthapuram, Trichy, Vishakhapatnam

Follow us :



www.ralliwolf.com  +91 90734 93011