Ralli Wolf





MIG SERIES



MMA









Specifications

Products Type	MIG 200S
Model	RM20
Input Voltage (V)	AC 220 ± 15%
Frequency (HZ)	50/60
Rated Input Current (A)	37.7
Power (KVA)	8.2
Output Current Range (A)	50-200
Rated Output Voltage (V)	16.5-26.5
Duty Cycle (%)	60
Power Factor	0.73
Efficiency (%)	80
Wire-feeding Speed (m/min)	2.5-18
Wire Diameter	0.8
Output Cable (mm)	25+
MMA Facility	Available
Inverter Technology	IGBT
Type Wire Feeder	In-Built
Net Weight (Kg)	30

Features

- · This inverter's stable arc is suitable for almost any welding need
- · Portable and Easy to Operate
- · Efficient and energy saving
- Minimal spatter, deep penetration, beautiful welding seam With Advanced IGBT Technology

Standard Accessories





^{*} In view of continuous development RALLIWOLF reserves the right to modify / alter the design / modification without prior notice

Ralli Wolf Industries Ltd.

(Formerly Ralli Engineering Ltd)

An ISO 9001: 2015 certified Organisation

Regd. Office: 4, Fairlie Place Kolkata - 700001 (India), E: info@ralliwolf.com, P: +91 33 2262 7341

SALES NETWORK: Ahmedabad | Akola | Baroda | Bangalore | Bhubaneswar | Bhopal | Chennai | Coimbatore | Cuttack | Delhi Faridabad | Guwahati | Indore | Jaipur | Jamshedpur | Kolkata | Ludhiana | Mumbai | Nagpur | Pune | Raipur | Secunderabad | Trichy