

CUT 160 AIR PLASMA CUTTING

Features

- Plasma cutting
- 2T/4T switch
- Over current LED
- Digital display

MODEL: **RC 16**



Technical Specifications:

Model	: RC16
Input Voltage (V)	: 415V $\pm$ 15%
Frequency (HZ)	: 50/60
Rated Input Current (A)	: 44
Power (KVA)	: 29
No-load Voltage (V)	: 320
Output Current Range (A)	: 20-160
Rated Output Voltage (V)	: 144
Duty Cycle (%)	: 60

No-load Loss (W)	: 85
Efficiency (%)	: 85
Power Factor	: 0.93
Insulation Grade	: F
Housing Protection Grade	: IP 21
Arcing Way	: Pilot arc transfer
Required Air Pressure (Kg/cm ²)	: 4-6
Cutting Thickness (mm)	: 1-50
Net Weight (Kg)	: 60

Ralli Wolf Industries Ltd.

An ISO 9001 : 2015 certified Organisation

Corporate Office :

Diamond Heritage, 510, 5th Floor,
16, Strand Road, Kolkata - 700001 (India)
E : info@ralliwolf.com, P : +91 81000 80353
CIN : U51109WB1996PLC077080

Sales Network :

Ahmedabad, Bangalore, Baroda, Bhopal, Chennai, Coimbatore, Cuttack, Delhi, Gurgaon, Guwahati, Jaipur, Jamshedpur, Kolkata, Ludhiana, Mumbai, Nagpur, Pune, Secunderabad, Siliguri, Thiruvananthapuram, Trichy, Vishakhapatnam

Follow us :



www.ralliwolf.com  +91 81000 80353