

TIG SERIES

Features

- High Frequency ignition
- Superior ARC performance
- Post-flow function
- Light and compact, easy to carry and use
- Economies tungsten use with a stable output & high duty cycle

MODEL : **RT40**



Technical Specifications :

Model	: RT40	Efficiency (%)	: 85
Input Voltage (V)	: AC 415±15%, 3Ph 50Hz	Power Factor	: 0.93
Rated Input Current (A)	: 18.2/25.3	MMA Function	: Available
Power (KVA)	: 18.2	Inverter Technology	: IGBT
No-load Voltage (V)	: 70	Post-Flow (Sec.)	: 2.5
Output Current (A)	: 10-400	Arcing Way	: High Frequency
Rated Output Voltage (V)	: 36	Pre-Flow (Sec.)	: 0-5
Duty Cycle (%)	: 60	Net Weight (Kg)	: 29.5Kg
No-load Loss (W)	: 80		

NOTE :

- In View of continuous development, **Ralliwolf** reserves the right to modify/after the design and/or specification without any prior notice.
- Welding Accessories optional.

Ralli Wolf Industries Ltd.

An ISO 9001 : 2015 Certified Organisation

Regd. Office :

Diamond Heritage, 5th Floor,
16 Strand Road, Kolkata- 700 001, WB, India
✉ info@ralliwolf.com ☎ +91 81000 80353
CIN : U51109WB1996PLCO77080

Sales Network :

Ahmedabad, Bhilai, Bangalore, Bhubaneswar, Calicut, Chennai, Coimbatore, Cuttack, Gurgaon, Guwahati, Hamirpur, Indore, Jamshedpur, Jammu, Jaipur, Kanpur, Kolkata, Kolhapur, Kochi, Lucknow, Mumbai, Madurai, Nagpur, New Delhi, Pune, Raipur, Siliguri, Secunderabad, Vadora, Varanasi, Visakhapatnam

Follow us :



www.ralliwolf.com +91 81000 80353