

FCT SERIES

Features

- Robust coil design for long service life
Superior dynamic characteristics
- High metal recovery ■ Uniform current scale
- Current indicator and controlling handle on front panel
- Two large rear wheels with front Castor/Stay
- Conforms to IS -1851
- Fitted with ON/OFF Switch

MODEL: **FCT600**



Technical Specifications:

Products Type	: ARC 600	MCHWC (60%)	: 500A
Model	: FCT 600	MAWC (100%)	: 380A
Input Supply (V)	: AC 380/415/440V, 2 Lines of 3ph	Welding Current Control	: Stepless
Frequency (HZ)	: 50	Insulation Grade	: H
Rated Input Current (A)	: 94	Protection Grade	: IP-23
Rated Power (KVA)	: 39	Cooling	: Forced Cool
No-load Voltage (V)	: 80 (Max)	Technology	: Moving Core Type
Output Current Range (A)	: 60-600	Net Weight (Kg)	: 150kg
Rated Output Voltage (V)	: 44	Dimension in MM (LxWxH)	: 839x560x700
		Welding Accessories	: Optional

Applications : Suitable for General Purpose, Low Hydrogen, Stainless Steel Electrodes etc.

* In view of continuous development RALLIWOLF reserves the right to modify / alter the design / modification without prior notice

Ralli Wolf Industries Ltd.

An ISO 9001 : 2015 certified Organisation

Corporate Office :

Diamond Heritage, 510, 5th Floor,
16, Strand Road, Kolkata - 700001 (India)
E : info@ralliwolf.com, P : +91 81000 80353
CIN : U51109WB1996PLC077080

Sales Network :

Ahmedabad, Bangalore, Baroda, Bhopal, Chennai, Coimbatore, Cuttack, Delhi, Gurgaon, Guwahati, Jaipur, Jamshedpur, Kolkata, Ludhiana, Mumbai, Nagpur, Pune, Secunderabad, Siliguri, Thiruvananthapuram, Trichy, Vishakhapatnam

Follow us :



www.ralliwolf.com  +91 90734 93011